

# STAYCOLD HD690

High Performance  
Single Door  
Upright Cooler




## GREENSENSE FEATURES SAVING ENERGY AND REDUCING LIFETIME COSTS



### Digital Thermostat

For accurate temperature control and built in voltage protection.




### LED Lighting

Illuminating the interior of the unit for maximum visibility.



### EcoMate Foam

Water based blowing agent that is non-flammable and has zero ODP.



### Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.



Trust the Experience



# STAYCOLD HD690

## SINGLE DOOR COOLER

### CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Self-closing hinged doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors
- Reversible door action



Specifications		Internal Dimensions	
Climate Class	5	Height mm	1380
Nett Capacity (ltr)	455	Width mm	600
Shelves	4	Depth mm	550
Cooling Type	Forced air	<b>Packed Dimensions</b>	
Voltage/Hz	220/50	Height mm	2120
Refrigerant	R134a	Width mm	700
330ml Can Cap	560	Depth mm	645
330ml Bottle Cap	360	Weight (kg)	117
<b>External Dimensions</b>		<b>Container Loading</b>	
Height mm	2020	20'	27
Width mm	690	40'	54
Depth mm	635		
Code	Model	Description	
2150	HD690	Std model with black trim and white Chromadek	
2153	HD690-LFS	S/S sides, hydrocarbon (R290) gas, and grey trim	
4150	SHD690	Stainless steel sides and solid door with grey trim	

 1 Kakie Strachan Rd  
Parys, South Africa

 +27 (56) 819 8097

 [info@staycold.co.za](mailto:info@staycold.co.za)

 [www.staycold.co.za](http://www.staycold.co.za)

 Staycold International (Pty) Ltd



In the interests of continuous product development, specifications may be changed without notice.