

# STAYCOLD SD1140

*High Performance  
Double Sliding Door  
Upright Cooler*




## GREENSENSE FEATURES

SAVING ENERGY AND REDUCING LIFETIME COSTS



### Digital Thermostat

For accurate temperature control and built in voltage protection.



### LED Lighting

Illuminating the interior of the unit for maximum visibility.



### EcoMate Foam

Water based insulation foam that is non-flammable and has zero ODP.



### Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.



Trust the Experience



# STAYCOLD SD1140

## DOUBLE DOOR COOLER

### CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Reliable, self-closing sliding doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors



Specifications		Internal Dimensions	
Climate Class	5	Height mm	1380
Nett Capacity (ltr)	746	Width mm	1050
Shelves	8	Depth mm	515
Cooling Type	Forced air	Packed Dimensions	
Voltage/Hz	220/50	Height mm	2120
Refrigerant	R134a	Width mm	1150
330ml Can Cap	980	Depth mm	645
330ml Bottle Cap	640	Weight kg	180
External Dimensions		Container Loading	
Height mm	2020	20'	18
Width mm	1140	40'	36
Depth mm	635		
Code	Model	Description	
2070	SD1140	Std model with black trim and white Chromadek	
2073	SD1140-LFS	S/S sides, hydrocarbon (R290) gas and grey trim	

 1 Kakie Strachan Rd  
Parys, South Africa

 +27 (56) 819 8097

 [info@staycold.co.za](mailto:info@staycold.co.za)

 [www.staycold.co.za](http://www.staycold.co.za)

 Staycold International (Pty) Ltd



In the interests of continuous product development, specifications may be changed without notice.