

STAYCOLD SD890

*High Performance
Double Sliding Door
Upright Cooler*




GREENSENSE FEATURES

SAVING ENERGY AND REDUCING LIFETIME COSTS



Digital Thermostat

For accurate temperature control and built in voltage protection.



LED Lighting

Illuminating the interior of the unit for maximum visibility.



EcoMate Foam

Water based insulation foam that is non-flammable and has zero ODP.



Low-E Glass Door

Improved glass insulation lowers running costs and reduces condensation.



Trust the Experience



STAYCOLD SD890

DOUBLE DOOR COOLER

CABINET FEATURES

- Fully adjustable shelving
- LED lighting internal and canopy
- Energy saving EMD as standard
- High efficiency compressor
- High performance heat exchangers for powerful cooling
- Reliable, self-closing sliding doors
- Non-flammable, water based polyurethane blowing agent
- Double tempered, thermopane Low-E glass doors



Specifications		Internal Dimensions	
Climate Class	5	Height mm	1380
Nett Capacity (ltr)	569	Width mm	800
Shelves	8	Depth mm	515
Cooling Type	Forced air	Packed Dimensions	
Voltage/Hz	220/50	Height mm	2120
Refrigerant	R134a	Width mm	900
330ml Can Cap	700	Depth mm	645
330ml Bottle Cap	480	Weight kg	149
External Dimensions		Container Loading	
Height mm	2020	20'	21
Width mm	890	40'	44
Depth mm	635		
Code	Model	Description	
2060	SD890	Std model with black trim and white Chromadek	
2063	SD890-LFS	S/S sides, hydrocarbon (R290) gas and grey trim	

 1 Kakie Strachan Rd
Parys, South Africa

 +27 (56) 819 8097

 info@staycold.co.za

 www.staycold.co.za

 Staycold International (Pty) Ltd



In the interests of continuous product development, specifications may be changed without notice.